



Ball Float

PROTECTION FOR GAS SAMPLING SYSTEMS

Product Overview

For a confined space clearance measurement, a sampling hose is attached to a pumped gas detector. An open end of the hose, runs the risk of allowing dust and liquids to enter the sampling hose, blocking the hose and delaying the work. Ball floats are a perfect way to ensure no liquid or dust can enter the sampling hose.

WatchGas has completely redeveloped the ball float to make it suited to heavy duty work in every way.

The ball float is made in one piece to make it more resistant and durable in comparison to ball floats that are made from two hemispheres glued together. The material is chemical-resistant, antistatic and non-adsorbent, therefore it does not interfere with your measurement. Also, its bright yellow color makes it visible, providing contrast in dimly-lit situations.

We believe we have developed the best ball float. But the best part is that it's very competitively priced. Give us a call or visit our website to find the nearest distributor.

Ball Float Specifications

Size	60 x 65 mm
Material	High Density Polyethylene
Safety Certifications	IEC/TS 60079-32-1: 2015, IEC 61340-4-4, Nationaler Brandschutz NFPA 77 (2013) / EN-60079-0 EAN-13 Code: 8719992974764
Suitable For	3x5 mm Sampling Hose 5x8 mm Sampling Hose

For more information

www.watchgas.com / www.watchgasusa.com
 info@watchgas.com / info@watchgasusa.com

WatchGas Ball Float DS EN V1.0F1F © 2026 WatchGas B.V.

WatchGas is dedicated to continuously improving its products. Therefore, the specifications and features mentioned in this datasheet are subject to change without prior notice.

Distributed by: